

[Web](#) [Images](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more ▼](#)
[Sign in](#)

Google

dynamic select checksum algorithm variable

Search

[Advanced Search](#)
[Preferences](#)

Web

Results 1 - 10 of about 40,200 for [dynamic select checksum algorithm variable](#). (0.20 seconds)

[Enable "cdr check" functionality within IBM Informix Dynamic Server](#)

Apr 6, 2006 ... For example, the environmental variable %MSDevDir% should be set to ...
 EOF Select checksum (iname, 0), checksum (iname, 0) from customers; ! ...
[www-128.ibm.com/developerworks/db2/library/techarticle/dm-0604pnet/](#) - 43k -
[Cached](#) - [Similar pages](#)

[The Data Charmer: Seeking alternatives to cursors](#)

Mar 9, 2006 ... Using a SELECT statement getting the checksum of each row, we start with
 a empty user variable, and we merge that result to the user ...
[datacharmer.blogspot.com/2006/03/seeking-alternatives-to-cursors.html](#) - 110k -
[Cached](#) - [Similar pages](#)

[A dynamic web agent for verifying the security and integrity of a ...](#)

The checksum algorithm in the BIBLINK project is. limited to extraction of specific ...
 numeric value representing a message of variable size p [23]. ...
[ieeexplore.ieee.org/iel5/7500/20395/00942261.pdf?arnumber=942261](#) - [Similar pages](#)

[makefile -*- # The file Setup is used by the makesetup script to ...](#)

The necessary files # md5c.c and md5.h are included here. md5 md5module.c md5c.c # The
 sha module implements the SHA checksum algorithm. ...
[www.cse.monash.edu.au/~nimrod/nimrodg/Setup-2.2.x.dist](#) - 17k - [Cached](#) - [Similar pages](#)

[makefile -*- # The file Setup is used by the makesetup script to ...](#)

If # you're on a platform that doesn't support dynamic loading. ... #md5 md5module.c md5c.c
 # The sha module implements the SHA checksum algorithm. ...
[svn.python.org/projects/python/branches/gen-branch/Modules/Setup.dist](#) - 17k -
[Cached](#) - [Similar pages](#)

[RFC 4030 - The Authentication Suboption for the Dynamic Host ...](#)

The checksum is usually a digest of the data in the DHCP packet computed by using the
 method specified by the Algorithm field. 5. ...
[tools.ietf.org/html/rfc4030](#) - 49k - [Cached](#) - [Similar pages](#)

[Fedora Administrative GUI Client](#)

When you select a checksum algorithm from the drop down box, you will notice that a ... to
 the digital object to provide dynamic view of datastream content. ...
[www.fedora-commons.org/documentation/2.2.2/userdocs/client/admin-gui/index.html](#) - 520k -
[Cached](#) - [Similar pages](#)

[How to calculate table checksums in MySQL at Xaprb](#)

Jan 25, 2007 ... SELECT will place shared locks on every row in the table. ... list from
 INFORMATION_SCHEMA and generate the dynamic SQL to checksum a table. ...
[www.xaprb.com/blog/2007/01/25/how-to-calculate-table-checksums-in-mysql/](#) - 50k -
[Cached](#) - [Similar pages](#)

[RFC 4030 \(rfc4030\) - The Authentication Suboption for the Dynamic ...](#)

The Authentication Information field contains the data required to communicate algorithm-
 specific parameters, as well as the checksum. ...
[www.faqs.org/rfcs/rfc4030.html](#) - 35k - [Cached](#) - [Similar pages](#)

[\[4suite\] 4XPath demo core dump](#)

The STDWIN variable must point to the # STDWIN toplevel directory. ... here. md5
 md5module.c md5c.c # The sha module implements the SHA checksum algorithm. ...

lists.fourthought.com/pipermail/4suite/2000-March/000072.html - 20k -
Cached - Similar pages

1 2 3 4 5 6 7 8 9 10 Next

[Make Google your homepage](#)

[dynamic select checksum algorithm variable](#)

[Search](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#) | [Try Google Experimental](#)

©2008 Google - [Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)